

## HIGH-SPIN Washer Extractor model: MAQ2 A 60C E - TC2

### DRUM

Load Capacity	Kg	60
Drum Volume	Lt	590
Basket diameter	Ø	1048
Depth basket	mm	680
Washing Speed	rpm	38
Extraction Speed	rpm	875
"G" Factor		450
Noise Level	Db	<70

### LOADING DOOR

Height Center door	mm	1170
Door diameter	Ø	560

### POWER

Motor power	Kw	15
Electric Heating	Kw	36
Total Power for ELECTRIC Version	Kw	51
Total Power for HOT WATER Version	Kw	15

### CONNECTIONS

Drain water	Ø	3"
Water inlet	Ø	1"
Water Pressure	Bar	2 ÷ 4

### MACHINE DIMENSIONS

Front Width	mm	1420
Depth	mm	1433
Height	mm	1890
NET Weight	Kg	1454

### MACHINE DIMENSIONS with PACKING

Front Width	mm	1600
Depth	mm	1595
Height	mm	1930
GROSS Weight	Kg	1544
Volume	mt3	4,9

- Load Capacity: **60 Kg.**
- Type of Heating: **ELECTRIC and HOT WATER**
- Voltage: V. 400 / 3 Ph / 50 Hz.
- Extraction Speed: **875 Rpm**
- G Factor = 450
- Microprocessor Touch Screen: TC2 Type
- Possibility of programming, export and import program through USB memory without limits.
- WET CLEANING System
- 26 Preset Programs
- Multilingual, including English and Vietnamese.
- 8 signals for automatic liquid dosing, programmable in time and delay
- Free Standing high-spin machine
- Emergency stop button, Safety switch for door opening
- These machines have electronic control of imbalance with Electronic frequency variator, that detects the load uncentered before spinning
- Wash and Spin speeds are configurable.
- Complete regulation of water levels
- Alarm display
- Very low water consumption
- Detergent dispenser with 4 compartments (pre-wash, wash bleachers and softeners)
- 3 Water inlets (Hot water, Cold water, Soft water)
- Grey Skin plate body
- Vat, drum in stainless Steel AISI 304



**NOT NEED ANCHORING TO THE FLOOR**